

DECKGARD STRIPPER

For use on PVC synthetic decking and rubber. Designed to cut through and break up old emulsion polishes. It penetrates layers of dirt and polish, breaking up and emulsifying the old film ready for easy removal.

Directions For Use

Dilute 1 part Deckcare Stripper to 8 parts of water for emulsion stripping. For heavy build-up, the quantity of water may be reduced, with a maximum contact time of 3-5 minutes.

1. Clean the deck by section to avoid having to walk onto treated area - which may become slippery. Apply dilute solution freely with a sprayer, mop or brush.
2. Allow the chemicals to soften the old DeckGard and dirt (usually 3-5 minutes).
3. Apply more hot water, then scrub using a nylon stripping pad under a machine or by hand with a brush. Pick up slurry then rinse deck.
4. Finally, thoroughly rinse entire deck again several times with clean water.
5. Allow to dry.

Ensure any splashes are wiped up as neat product could discolour certain types of rubber.

Health & Safety

Danger. Causes severe skin burns and eye damage. Do not breathe vapour/spray.

Wash contaminated skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. Wash contaminated clothing before reuse. Dispose of contents/container in accordance with national regulations. Contains DISODIUM METASILICATE, 2-AMINOETHANOL, POTASSIUM HYDROXIDE. Store locked up.

UN1760 Corrosive Liquid N.O.S (Potassium Hydroxide & Disodium Trioxosilicate) 8 PGII

